

TUBE DRIVE

TWIN TRIODE
DUAL OVERDRIVE



INPUT REMOTE IN OUTPUT

THUMB SCREW / PUSH ROD - FOR TUBE REMOVAL
(USE INCLUDED ALLEN KEY TO REMOVE TOP SHROUD)

9VDC - 500mA Center Negative



CONTROLS

TUBE SIDE

TWIN TRIODE
BASED OVERDRIVE

LEVEL

AUDIO BALANCING
CLOCKWISE FOR MORE VOLUME

GAIN

HARMONIC CONTENT
CLOCKWISE FOR MORE GAIN

TONE

LOW PASS FILTER
CLOCKWISE FOR MAX TREBLE



DRIVE SIDE

THE LEGENDARY
KEELEY PHAT MOD

LEVEL

AUDIO BALANCING
CLOCKWISE FOR MORE VOLUME

DRIVE

HARMONIC CONTENT
CLOCKWISE FOR MORE DRIVE

TONE

LOW PASS FILTER
CLOCKWISE FOR MAX TREBLE

TRUE BYPASS OR BUFFERED SWITCHING

PRESS AND HOLD TUBE FOOTSWITCH FOR 2 SECONDS

2 FLASHES - TRUE BYPASS • 3 FLASHES - BUFFERED (FACTORY DEFAULT)

ORDER SWITCHING

PRESS AND HOLD DRIVE FOOTSWITCH FOR 2 SECONDS

CHANNEL THAT FLASHES IS FIRST IN THE CHAIN

REMOTE CONTROL

TRS CONNECTION, GROUNDING EITHER TIP OR RING TO ACTIVATE

TIP - DRIVE SIDE • RING - TUBE SIDE

FACTORY RESET

TO RESET THE TUBE DRIVE TO FACTORY DEFAULT

PRESS AND HOLD BOTH FOOTSWITCHES
WHILE APPLYING POWER TO THE UNIT



HIGH VOLTAGE
DO NOT OPEN



ENGINEERED, DESIGNED, AND BUILT IN THE USA

PLEASE
DISCONNECT
POWER BEFORE
SERVICING