

Thanks for buying the Morley Twin Mix

The Twin Mix is designed to route two input signals to two output sources. Each input has its own level control to balance different input levels. Each input also has a mute switch. LED Indication show which input signal is engaged or muted. When using only Output A, both inputs are combined and routed to output A. When using both Output A and Output B, each input is routed to it's own output (Input 1 goes to Output A, Input 2 goes to Output B).

While there are countless uses for the Twin Mix, below are a few examples to get you started. Unity gain is at approximately 10 o'clock on each input knob. From 10 o'clock to 1 o'clock, will add clean boost and turning up beyond 1 o'clock will add slight overdrive. The Twin Mix powers up from one 9V battery or optional Morley® 9V 300mA adapter (center polarity is negative). Remove bottom cover via 4 Phillips head screws to gain access to battery compartment

This product is warranted for two years from date of purchase. To obtain warranty service, please call Morley® customer service toll free at 1-800-284-5172 ext 15 or email us at info@morleypedals.com

Hooking two output sources together via the Twin Mix may create Ground Loop Hum in one or more of the output sources, this is a normal occurrence and can be easily solved. Please visit www.ebtechaudio.com for information on why Ground Loops occur, tips on diagnosing hum and learn about products that solve hum and signal problems.

IMPORTANT NOTE: THIS DEVICE IS INTENDED FOR USE WITH PASSIVE AUDIO SIGNALS, DO NOT USE THIS DEVICE ON POWERED SPEAKER LINES OR YOU WILL DAMAGE THE AMP AND/OR SPEAKER.



Example #1



Example #2



Example #3

This product is proudly made in the U.S.A.

Sound Enhancement Products, Inc. 325 Cary Point Drive Cary IL 60013

www.morleypedals.com